

Архангельск (8182)63-90-72
 Астана +7(7172)727-132
 Белгород (4722)40-23-64
 Брянск (4832)59-03-52
 Владивосток (423)249-28-31
 Вологда (844)278-03-48
 Волгоград (8172)26-41-59
 Воронеж (473)204-51-73
 Екатеринбург (343)384-55-89
 Иваново (4932)77-34-06
 Ижевск (3412)26-03-58
 Казань (843)206-01-48

Калининград (4012)72-03-81
 Калуга (4842)92-23-67
 Кемерово (3842)65-04-62
 Киров (8332)68-02-04
 Краснодар (861)203-40-90
 Красноярск (391)204-63-61
 Курск (4712)77-13-04
 Липецк (4742)52-20-81
 Магнитогорск (3519)55-03-13
 Москва (495)268-04-70
 Мурманск (8152)59-64-93
 Набережные Челны (8552)20-53-41

Нижний Новгород (831)429-08-12
 Новокузнецк (3843)20-46-81
 Новосибирск (383)227-86-73
 Орел (4862)44-53-42
 Оренбург (3532)37-68-04
 Пенза (8412)22-31-16
 Пермь (342)205-81-47
 Ростов-на-Дону (863)308-18-15
 Рязань (4912)46-61-64
 Самара (846)206-03-16
 Санкт-Петербург (812)309-46-40
 Саратов (845)249-38-78

Смоленск (4812)29-41-54
 Сочи (862)225-72-31
 Ставрополь (8652)20-65-13
 Тверь (4822)63-31-35
 Томск (3822)98-41-53
 Тула (4872)74-02-29
 Тюмень (3452)66-21-18
 Ульяновск (8422)24-23-59
 Уфа (347)229-48-12
 Челябинск (351)202-03-61
 Череповец (8202)49-02-64
 Ярославль (4852)69-52-93

Единый адрес для всех регионов: azs@nt-rt.ru || www.asea.nt-rt.ru

FEATURE

- Compact design of small size and light weight
- Circuit installation for electric shock prevention
- Based on IGBT technology, stable arc by inverter control
- Cut all conductive metals only with compressed air and electric power.
- Heat-affected zone is narrow and heat strain is very rare..
- Beginners also could cut easily, according to contact/non-contact cutting way.



SPECIFICATIONS 정/격/사/양

MODEL	71P	Aircomp+70P	100P	130P	150P
Rated input voltage 정격 입력 전압	220V, 1Ph	220V, 1Ph	220V/380V 1Ph/3Ph both	220V/380V 1Ph/3Ph both	220V/3Ph or 380V/3Ph only
Rated frequency 정격 주파수	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Rated output current 정격 출력 전류	71A	70A	100A	130A	150A
Rated input capacity 정격 용량	8.1KVA	8.4KVA	19KVA	26KVA	30KVA
Load voltage 부하 전압	130V	130V	140V	150V	150V
Maximum no-load voltage 최고 무부하 전압	< 280V	< 280V	< 290V	< 290V	< 270V
Duty cycle 정격 사용율	60%	60%	40%	40%	40%
Maximum cutting capacity 최대 절단 두께	10mm	8mm	15mm	20mm	30mm
Dimension(WxDxH) 치수	170x490x280	250x560x360	375x700x600	375x700x600	380x760x680
Weight 중량	17Kg	28Kg	48Kg	52Kg	70Kg