

Архангельск (8182)63-90-72
 Астана +7(7172)727-132
 Белгород (4722)40-23-64
 Брянск (4832)59-03-52
 Владивосток (423)249-28-31
 Волгоград (844)278-03-48
 Вологда (8172)26-41-59
 Воронеж (473)204-51-73
 Екатеринбург (343)384-55-89
 Иваново (4932)77-34-06
 Ижевск (3412)26-03-58
 Казань (843)206-01-48

Калининград (4012)72-03-81
 Калуга (4842)92-23-67
 Кемерово (3842)65-04-62
 Киров (8332)68-02-04
 Краснодар (861)203-40-90
 Красноярск (391)204-63-61
 Курск (4712)77-13-04
 Липецк (4742)52-20-81
 Магнитогорск (3519)55-03-13
 Москва (495)268-04-70
 Мурманск (8152)59-64-93
 Набережные Челны (8552)20-53-41

Нижний Новгород (831)429-08-12
 Новокузнецк (3843)20-46-81
 Новосибирск (383)227-86-73
 Орел (4862)44-53-42
 Оренбург (3532)37-68-04
 Пенза (8412)22-31-16
 Пермь (342)205-81-47
 Ростов-на-Дону (863)308-18-15
 Рязань (4912)46-61-64
 Самара (846)206-03-16
 Санкт-Петербург (812)309-46-40
 Саратов (845)249-38-78

Смоленск (4812)29-41-54
 Сочи (862)225-72-31
 Ставрополь (8652)20-65-13
 Тверь (4822)63-31-35
 Томск (3822)98-41-53
 Тула (4872)74-02-29
 Тюмень (3452)66-21-18
 Ульяновск (8422)24-23-59
 Уфа (347)229-48-12
 Челябинск (351)202-03-61
 Череповец (8202)49-02-64
 Ярославль (4852)69-52-93

Единый адрес для всех регионов: azs@nt-rt.ru || www.asea.nt-rt.ru

→ FEATURE

- Compact design including all functions of Argon TIG with small size and light weight.
- Built-in circuit installation for electric shock prevention.
- Based on IGBT technology, promoted stable arc by inverter control
- Crater on/off/repeat function installed
- Gas check and After-gas adjusting timer installed.
- With arc holder connected, you can also use for manual welding.



→ SPECIFICATIONS 정/격/사/양

MODEL	200TIG	300TIG	350TIG	500TIG
Rated input voltage 정격 입력 전압	220V, 1Ph	220V, 1Ph	220V/380V 1Ph/3Ph both	220V/380V 1Ph/3Ph both
Rated frequency 정격 주파수	60Hz	60Hz	60Hz	60Hz
Rated output current 정격 출력 전류	5~200A(TIG) 40~160A(MMA)	5~300A(TIG) 60~220A(MMA)	5~350A(TIG) 70~250A(MMA)	5~500A(TIG) 70~400A(MMA)
Rated input capacity 정격 용량	4.4KVA	8KVA	10KVA(3Ph)	18KVA(3Ph)
Load voltage 부하 전압	13V	14V	24V	24V
Maximum no-load voltage 최고 무부하 전압	< 78V	< 78V	< 75V	< 75V
Duty cycle 정격 사용율	60%	60%	60%	60%
Dimension(WxDxH) 치수	160x430x270	190x480x270	260x430x440	375x700x600
Weight 중량	15Kg	17Kg	25Kg	49Kg